

SECTION 5.4

100%
RECYCLABLE




BARRIER

LOK-UP (No Parking or No Entry)

Lok-up is a collapsible steel parking and vehicle access barrier that locks in both the up and down positions. Steel construction and large footprint ensure maximum strength and durability. The minimum closed height of 35mm opens up to a working height of 750mm. A large reflective sign face and safety yellow powder coated finish provide maximum visibility day or night.

Value features:

- » Available in 2 different models.
- » Zinc plate and safety yellow powder coat.
- » It stands tall when locked up. 750mm tall.
- » It lays low when locked down. 35mm low.
- » Comes complete with padlock and fixings.
- » Large footprint for strong positive mounting into concrete or asphalt.
- » Reflective sign face for night visibility.
- » Locks in both the up and down positions.



Specifications

Description:	Lock up / Lock down parking and access barrier.
Material:	4mm Mild Steel.
Finish:	Zinc plated & Powder coated.
Height:	Down 35mm. / Up 750mm.
Weight:	Operating 6kgs approx. / Shipping 15.4kgs.
Fixing:	Masonry anchors (supplied).
Locking:	40mm brass padlock (supplied).

PART No.	DESCRIPTION
LU-NP	Lok-up with NO PARKING sign
LU-NE	Lok-up with NO ENTRY sign



05

SECTION 5.5

100%
RECYCLABLE



FOLD DOWN BOLLARD

Our Fold Down Bollard model FD150 has been designed for applications such as vehicle access control and parking space protection. When laying flat, the FD150 is only 80mm high allowing sufficient vehicle clearance.

When upright, it stands 800mm high with a broad face of 150mm wide for greater visibility. This broad face includes a reflective sign face.

Available as a surface mount model or can be used with an in-ground kit (BGK4) for setting into new concrete.

Now available in either padlock or key lockable models.

Value features:

- » Stands 800mm tall when locked up.
- » Only 80mm high in the lay flat position.
- » Available in surface mount or used with concrete footing kit.
- » Padlock lockable model includes fixings and padlock.
- » Key lockable model includes fixings and two keys.
- » Hot dip galvanised and finished in high visibility safety yellow powder coat.
- » Broad 150mm face includes reflective sign face.



Now hot dip galvanised.



FDS150 – Padlock



FDS150K – Key lockable

Specifications:

Description:	Fold down access and parking barrier.
Material:	Mild steel.
Finish:	Safety yellow powder coat or galvanised.
Height:	Down 80mm / Up 800mm.
Weight:	Operating 5kg. / Shipping 12kg.
Fixing:	Surface mount supplied with 4 off 12 x 60mm. Masonry anchors.
Locking:	40mm padlock (supplied) or key lockable.
Sign:	Class 2 reflective sheeting 120 x 500mm (included).



FDS1 – reflective sign face

PART No.	DESCRIPTION
FD150	Fold down bollard 150 x 50 x 800mm – Padlock lockable
FD150K	Fold down bollard 150 x 50 x 800mm – Key lockable
FD150-G	Fold down bollard 150 x 50 x 800mm – Galvanised
FDS1	Reflective sign face with Red & Yellow diagonal stripes
BGK4	Concrete footing kit for FD150