

Replaces all previous versions

Effective 1st August 2004

## WHEEL TRACK

### Versatile Wheel Track

These lightweight wheels tracks can be used in a wide variety of warehousing and materials handling situations. Available in 75mm or 150mm pitch models they are ideal for use in warehousing shelving for the deep storage of parcels. As the front parcel is removed, the whole line moves up to take its place. The simple design has a line of conveyor wheels mounted in a 2mm pressed steel frame with provision for mounting to any flat surface. The standard 3000mm long tracks can be cut to any length to suit specific installations. By using the tracks mounted on Lemcol Rigid Supports a mini conveyor line can easily be set up, and altered to suit all kinds of materials handlings situations.

**Example:** Hard to handle cylindrical goods can be easily transported by mounting three Lemcol Wheel Tracks together (one at the bottom and one on each side).

LENGTH	PITCH	STEEL WHEEL	NYLON WHEEL
3000	75	L1660-3	L2660-3
3000	150	L1660-6	L2660-6


### WHEEL CONVEYOR / TRACK REPLACEMENT WHEELS

							PART NO.
STEEL	50	15	36	25	6.5		28444
NYLON	50	15	25	25	6.5		54225


### Ball Transfer Units

These simple, but very adaptable free-rolling units provide the capability to easily re-direct goods in any direction with minimum effort. Operators can transfer any flat object in any direction on a horizontal plane. They are especially suited for transferring goods from one conveyor line to another, the movement of boxes of parts around machines and manipulating heavy steel plates around presses and guillotines. They also serve as multi-directional switches and transfer stations for heavy flat objects.

**L1753**  
Capacity 45kg



**L1754**  
Capacity 90kg



### Inverted Castors

Complete floors of inverted castors enable easy multi-directional movement of large cargo containers and palletised storage bins with the minimum of effort. The castors feature wide radius nylon wheels with roller bearings. Wheel threadguards protect the bearings from the invasion of binding material. The swivel shroud also resists the ingress of dirt and moisture. LL65 and LH65 feature forged mounting plates that are fully machined and hardened for the severest of conditions. The more economical LC65 and LD65 have a heavy pressed steel mounting plate.

								MODEL
65	35	325	ROLLER	NYLON	96	63		LL65
65	35	325	ROLLER	NYLON	102	63		LH65
65	35	220	ROLLER	NYLON	96	76		LC65
65	35	220	ROLLER	NYLON	102	76		LD65



### Wheel Tracks, Transfer Units



**Catalog Page 44**