

MODEL B

The Flagship of All Carriers

MODELS*	B2-48-36	B2-48-48
TYPE	Electric	Electric
SPEED STANDARD (MPH)	11 (17.7 km/hr)	16 (25.7 km/hr)
RANGE (MILES)	24	24
LOAD CAPACITY (lbs)	3,000 (1360 kg)	3,000 (1360 kg)
BED SIZE (W"xL")	41"x75" (104x190 cm)	41"x75" (104x190 cm)
VOLTAGE	36	48

Based on Standard Configuration
 *Typical capacity: Actual load capacity depends on application and vehicle configuration



Tough and Dependable Product Solutions

The Model B series product line of Electric Personnel and Burden carriers offers the ultimate versatility in load capacity, vehicle configuration and vehicle performance. This unique modular vehicle design allows configurations to provide precise solutions to your needs.

The Model B series, equipped with GT electric drive train, provides years of reliability with low operating costs. Our worldwide sales staff is trained to discuss your needs and then configure a Model B to realize the most cost effective solution. This customization of products provides the best value for our customers.

Taylor-Dunn® with a team of worldwide dealers pride ourselves in providing multiple solutions in single product configuration. Whether your application is carrying loads, towing loads, moving personnel, or all three, we can configure a single product to meet all your needs.

The Model B can be configured to carry up to 4,000 lbs. of load, pull 17,500 lbs. or carry up to 10 people. Equipped with an automotive differential available with either 36 or 48 volt, the Model B is one of the best values for your utility applications.

With more than 150,000 vehicles in service and over 50 years of experience in the industry, Taylor-Dunn® products are the best way to go about your business.

Vehicles may be shown with optional equipment



TAYLOR-DUNN®
 Commercial and Industrial Vehicles Since 1949

The best way to go about your business

PERSONNEL CARRIERS



Aristocrat



Roadmaster



Taylortruck



Loadmaster



Model B Series



Electruck



Maintenance Expediter



Stepsaver



Stockchaser

TOW TRACTORS



Towmaster



Mule






Pullmaster



Model E



Huskey



MODEL B STANDARD SPECIFICATIONS*

Product Line	B2-48-36	B2-48-48
Unit Weight Lbs (Kgs)	1405 (637 kg)	1550 (702 kg)
Load Capacity Lbs (Kgs)	3000 (1360 kg)	3000 (1360 kg)
Battery Type	6 Ea., 6V, 217 Amp Hour	8 Ea., 6V, 217 Amp Hour
System Voltage	36V DC	48V DC
Drive Axle	GT Automotive Type, Differential	GT Automotive Type, Differential
Transmission	Oil Bath, Helical Gears	Oil Bath, Helical Gears
Motor	7.6 HP DC Separately Excited	9.7 HP DC Separately Excited
Tires	5.70 X 8, Pneumatic Load Range B	5.70 X 8, Pneumatic Load Range B
Brakes	2 Rear Wheel, Hydraulic Disc Standard	4 Wheel, Hydraulic Disc Standard
Steering	24:1 Ratio Automotive Type	24:1 Ratio Automotive Type
Frame	Unitized Fully Welded 16 GA Heavy Duty Diamond Plate Steel	Unitized Fully Welded 16 GA Heavy Duty Diamond Plate Steel
Bumper	Heavy Duty Steel Integrated Front & Rear Bumper	Heavy Duty Steel Integrated Front & Rear Bumper
Suspension	Leaf Spring Front & Rear With Dual Rear Shocks	Leaf Spring Front & Rear With Dual Rear Shocks
Color	Safety Orange	Safety Orange
Seats	Split Seat Cushion With Full Length Back Rest Covered With Black Vinyl	Split Seat Cushion With Full Length Back Rest Covered With Black Vinyl
Controller	Solid State, 36V	Solid State, 48V
Instrumentation	"Smart View Display" (Battery, Status Indicator, Hour meter, "Fault Code" display). Reverse Alarm	"Smart View Display" (Battery, Status Indicator, Hour meter, "Fault Code" display). Reverse Alarm
Light Accessories	Single Headlight, Dual Taillights w/Brakelights	Single Headlight, Dual Taillights w/Brakelights
Charger	25 Amp, 36V, Built In, Automatic w/Interlock	25 Amp, 48V, Built In, Automatic w/Interlock
Input Voltage	110/60 Hz.	110/60 Hz.
Conformance	Type E, ANSI B56.8, OSHA 1910.178, FM Approved	Type E, ANSI B56.8 OSHA 1910.178, FM Approved



MODEL B2-48-36-HC
Load capacity 4,000 lbs.; 4 wheel hydraulic brakes; soft solid tires; 11 mph speed

MODEL B2-54-36
Load capacity 5,000 lbs.; motor 11.5 HP Separately Excited intermittent duty 4 Wheel hyd. Disc Brakes; 18x5x14 solid cushion tires; overload springs and shock absorbers in rear; 8 mph speed.

MODEL B OPTIONAL FEATURES

- Charger**
- Portable 25 amp charger or 40 amp charger

- Accessories**
- Strobe light, amber - on pole, or top of cab
 - Dual headlights, directional signals
 - Hour meter, Automatic park brake

- Deck**
- 1,000 lb. capacity, electric hydraulic dump body
 - Stake sides, removable end gate, 14" high
 - 96 inch bed length (extended wheel base)
 - Welding tank cutouts
 - Steel sides and end gates, fold down
 - Steel panel cargo box

Battery Compartment

- 244 a.h. batteries
- Lift out battery box
- Roll out battery box

Hitches

- Automatic coupling, trailer
- Pintle trailer
- Ball hitch and bracket

Brakes

- Front wheel hydraulic disc (36V unit)

Cab

- Steel cab with doors
- Steel or vinyl doors for steel cab

- Fiberglass cab
- Vinyl doors for fiberglass cab

Top Covers

- Fiberglass or surrey top cover with tubular frame

Frame

- Foldaway seat for 2 additional passengers
- Permanent seating 4-6 passengers
- Smooth skin

Color

- Green, white, yellow or special paint colors
- Undercoating

* Based on standard configuration

Supplied by



www.spacepac.com.au

ph: 1300 763 444

Specifications, standard equipment, accessories and modifications subject to change without notice.