

Replaces all previous versions

Effective 1st December 2004

## TAYLOR DUNN - Utility Vehicles "UV"



Specifically designed to meet the needs of special or outdoor applications, Taylor-Dunn utility vehicles offer practical engineering matched with optimal performance. With speeds reaching 25 mph and load capacities up to 3,000 lbs., Taylor-Dunn will get you there safely and quickly, while reducing your operating and maintenance costs.



**TAYLORTRUCK**  
T-48-48



**ELECTRUCK®**  
ET-150-74  
ET-150-48



	Speed (Std. MPH)	Range (Miles)	Load Capacity (lbs.)	Towing Capacity (lbs.)	Bed Size (W" x L")	Voltage	Turning Radius (inches)
<b>ELECTRUCK®</b>							
ET-150-74	25 (max)	40	1,500	N/A	62 x 85	72	210"
ET-150-48	18	20	1,500	N/A	62 x 85	48	210"
<b>TAYLORTRUCK</b>							
T-48-48	19	30	3,000	10,000	41 x 75	48	145"
<b>ET3000</b>							
ET3000	19	30	3,000	10,000	41 x 75	48	145"



**SHUTTLEMASTER**  
B-050

**CARRYMASTER**  
B-125

**TOURMASTER**  
B-100



Commercial Vehicles are designed to provide economy and convenience in both industrial and commercial applications. If your needs are for moving people, the Tourmaster B-100 with 4-passenger, forward facing seating configuration is the most practical personnel carrier. The Carrymaster B-125 is a practical solution for carrying light loads. These features provide durability, reliability, and practicality to your business environment while reducing your operating and maintenance costs.

	Speed (Std. MPH)	Range (Miles)	Load Capacity (lbs.)	Towing Capacity (lbs.)	Bed Size (W" x L")	Voltage	Turning Radius (inches)
<b>COMMERCIAL VEHICLES</b>							
B-050	12	20	500	N/A	43 x 11	36	101"
B-100	12	20	800	N/A	43 x 11	36	132"
B-125	12	20	800	N/A	43 x 44	36	132"

All prices/specifications subject to change without notice.