

Marine Loading & Unloading Arms

Uses

- Loading And Unloading Products

Features

- Fully balanced via rigid link pantograph system with separated counterweight for inboard/outboard arm.
- Self-supported system provides the lowest weight and bending movement for easy handling.
- The world's lightest design available minimizes jetty costs.
- Designed to transfer all products; i.e., mineral oil, chemicals, liquefied gases.
- Available in carbon steel, low temperature steel, and stainless steel.
- Welded-in or flanged swivel joints.
- Seals available in Buna-N, Viton, PTFE, or any other material depending upon the application.
- Pressure rates of PN 10 to PN 40 or any other international standards. Higher pressure ratings available.
- Temperature ranging from -50°C (i.e., LPG) to +200°C (i.e., Bitumen). Other temperature criteria available.



The advantages in comparison with hose loading facilities are ease of handling, greater flexibility, less man power, minimum maintenance required, greater safety, and minimized operational cost to the owner.



We inspect, adjust, repair, and refurbish Marine Loading Arms! All brands...all ages!

Call to schedule an inspection



39 Ellen St. Wollongong NSW 2500, AUSTRALIA
Phone: +61 2 4227 3444 • 1300 763 444
Fax: +61 2 4226 2208 • ABN 98 002 454 462
spacepac@spacepac.com.au