

Mobile Process Workstands

Standard Features

- Industrial Type IA, 300 lb. duty rating.
- Meets and/or exceeds OSHA and ANSI requirements as we interpret them.
- Slip-resistant rubber treads attached to heavy-duty aluminum angle feet.
- Super heavy-duty aluminum construction. Designed and built to last.

Extra Heavy-Duty Aluminum Process Workstands 700 Series

- A Large 12" x 16" platform provides a comfortable work surface on which to stand for extended periods of time.
- 6" deep slip-resistant steps for added comfort and safety while climbing and working.
- 27 degree stair slope for easy climbing.
- Optional Tilt-N-Roll casters for easy repositioning and transporting.

MODEL	HEIGHT TO PLATFORM	PLATFORM SIZE	BASE SIZE	LBS.
720-20	20"	16" x 12"	21" x 24"	12
724-24	24"	16" x 12"	22" x 28"	13
730-30	30"	16" x 12"	24" x 32"	15
736-36	36"	16" x 12"	25" x 36"	16
748-48	48"	16" x 12"	27" x 43"	22



Double-Sided Non-Folding Aluminum Workstands 901-04 Series

- Can be climbed from either side.
- Large 19" X 22" one-piece embossed platform.
- Spring loaded, weight activated 3" casters allow easy positioning.
- 4" deep slip-resistant ribbed steps for a more comfortable work surface.

MODEL	HEIGHT TO PLATFORM	TOTAL HEIGHT	PLATFORM SIZE	BASE SIZE	LBS.
901-04	48"	68"	19" x 22"	25" x 51"	35



Mobile Process Workstands

500 lb. Capacity Super Heavy-Duty Aluminum Process Workstands 675 Series

300 lb. Capacity Extra Heavy-Duty Aluminum Process Workstands 601 Series

- Type 1A, 500 lb. load capacity.
- Solid channel side rail construction for superior strength.
- Extra large 20" X 20" slip-resistant coated platform adds utility and maximizes comfort for extended fixed height work.
- Extra heavy-duty aluminum skid plate feet protect side rails and provide a large contact area with the supporting surface.
- 27° slope with 10" risers and 6" deep step allows easier climbing and descent.
- 30" high handrail for added safety.
- 5" Tilt-N-Roll casters allow easy positioning and put all feet on the floor for climbing.
- 30" to 120" shipped fully assembled; 130" and 140" shipped "knocked down" to reduce freight costs.

- Type 1A, 300 lb. duty rated.
- Open side rail construction to maximize strength and minimize weight.
- Large 18" X 14" embossed platform provides a comfortable working surface.
- Heavy-duty aluminum angle feet with thick rubber treads help secure ladder during use.
- 27° slope with 12" risers and 6" deep step construction provides a functional platform stair ladder with a minimal footprint.
- 30" high handrail for added safety.
- 5" Tilt-N-Roll casters allow easy positioning and put all feet on the floor when climbing.
- Shipped fully assembled.



Optional Folding Handle



Optional Folding Handle



MODEL	HEIGHT TO PLATFORM	BOTTOM SIZE	LBS.
675-30	30"	24" x 40"	53
675-40	40"	25" x 47"	64
675-50	50"	26" x 54"	75
675-60	60"	27" x 61"	86
675-70	70"	29" x 68"	97
675-80	80"	30" x 71"	108
675-90	90"	31" x 81"	114
675-100	100"	32" x 88"	120
675-110	110"	33" x 95"	126
675-120	120"	35" x 102"	132
675-130	130"	36" x 109"	147
675-140	140"	37" x 116"	162

MODEL	HEIGHT TO PLATFORM	BOTTOM SIZE	LBS.
601-02	24"	22" x 30"	24
601-03	36"	23" x 37"	31
601-04	48"	25" x 45"	38
601-05	60"	26" x 52"	45
601-06	72"	28" x 60"	62
601-07	84"	29" x 67"	68
601-08	96"	31" x 75"	78
601-09	108"	32" x 82"	86
601-10	120"	34" x 90"	103
601-11	132"	35" x 97"	119
601-12	144"	37" x 105"	135