



Load Capacities up to 540kg

- Moulded from high grade resilient rubber
- Rayon bonded to provide added abrasive and spread resistance
- Cast iron centre for strength and durability
- Good load capacities
- Low noise levels
- Suitable for rough surface conditions with good shock absorbency
- Diameter range from 77mm to 305mm
- Normal operating temperature between -10°C and +60°C
- Australian made
- 12 month warranty

Users include: Workshops, Garages, Factories, Warehouses, Manufacturers

The Lemcol/Duncan wheel range is moulded from high grade resilient rubber, rayon bonded onto a cast iron centre.

The feature of rayon bonding is that it provides added abrasive and spread resistance. The use of a heavy duty, cast iron centre ensures a product of strength and reliability.

Rubber wheels combine the features of good load capacities, low noise level and the ability to withstand rough conditions. Their excellent resilient properties mean they eliminate vibrations transmitted through the wheel.

Diameter range from 77mm to 305mm, offered in a plain bore and supplied with sleeves to suit various imperial axle diameters.

Under normal operating conditions, the effective temperature ranges for rubber is between -10°C and +60°C.

12 Month Warranty

This range carries our standard 12 month warranty against faulty workmanship and materials, and is backed by a service and parts network Australia wide.



solid rubber

WHEELS

WHEEL SPECIFICATIONS

Dia. mm	Width mm	Capacity kg	Wheel Model No.	Bearing	Boss Width mm	Bore Dia. mm
77	25.4	21	ZZ311	Plain	35	12.7
89	38	32	ZZ314	Plain	38	19.05
89	38	32	ZZ316	Plain	38	12.7
89	38	32	ZZ317	Plain	38	15.87
102	38	44	ZZ324	Plain	38	12.7
102	38	44	ZZ320	Plain	38	15.87
102	38	44	ZZ321	Plain	38	19.05
127	38	60	ZZ325	Plain	41	12.7
127	38	60	ZZ326	Plain	41	15.87
127	38	60	ZZ328	Plain	41	22.2
127	51	120	ZZ331	Plain	57	19.05
127	51	120	ZZ330	Plain	57	25.4
152	38	122	ZZ339	Plain	41	12.7
152	38	122	ZZ337	Plain	41	15.87
152	38	122	ZZ336	Plain	41	19.05
152	38	122	ZZ335	Plain	41	22.22
152	38	122	ZZ338	Plain	41	25.4
152	50	190	ZZ340	Plain	57	12.7
152	50	190	ZZ341	Plain	57	15.87
152	50	190	ZZ342	Plain	57	19.05
152	50	190	ZZ343	Plain	57	22.22
152	50	190	ZZ344	Plain	57	25.4
203	38	240	ZZ354	Plain	41	15.87
203	38	240	ZZ356	Plain	41	19.05
203	38	240	ZZ357	Plain	41	22.2
203	38	240	ZZ358	Plain	41	25.4
203	51	320	ZZ363	Plain	57	15.87
203	51	320	ZZ360	Plain	57	19.05
203	51	320	ZZ361	Plain	57	22.22
203	51	320	ZZ362	Plain	57	25.4
229	51	320	ZZ367	Plain	57	25.4
254	51	480	ZZ371	Plain	60	19.05
254	51	480	ZZ370	Plain	60	25.4
305	51	540	ZZ375	Plain	60	19.05
305	51	540	ZZ376	Plain	60	25.4



SPACEPAC
INDUSTRIES Pty. Ltd.
 39 Ellen St. Wollongong NSW 2500, AUSTRALIA
 Phone: +61 2 4227 3444 • 1300 763 444
 Fax: +61 2 4226 2208 • ABN 98 002 454 462
spacepac@spacepac.com.au



WHEEL DIAM