

Replaces all previous versions

Effective 26th October 2006

H-SERIES 350kg Capacity MultiLift

Heavy duty Multi-purpose Lifter is an ideal alternative to the Fork Lift Truck and is capable of performing various lifting operations simply by exchanging attachments.

It is rated for 350 Kgs at a 350mm Load Centre and uses a single section, 'DuraGal' mast for maximum visibility and durability.

The MultiLift can be manufactured with almost any base configuration together with various mast height options. Standard attachments include Fixed Forks, Adjustable Forks, Slip-On-Platform or a three position Jib.

Maximum lift Height ranges: from 1500 to 2980mm depending on option fitted (see below)

Maximum Load	: 350KG
	at 350mm Load centre
Overall dimensions	: 2025Hx1000Lx680W mm
Base dimensions	: 680mmW (outside)
	525mmW (inside)
	100mm High
Base Unit Weight	: 54 kg



M/L-HY
Shown with Slip on Platform Option (SOP-HY)



Part Number	Descriptions
# M/L-HY	Multilift Base Unit 680mm o/a Width x 2025mm mast High - base unit without attachments
# PALM-HY	Pallet Multilift - Heavy Duty Base with 1206mm inside clearance, Complete with 1125mmLong Fixed Tynes w/ O/A tyne width of 630mm
# ML-BP-HY	Battery Powered Multilift Base unit without attachments



FIXED FORKS

Blade: 600Lx75Wx75H
 lowers to 100mm
 Raises to 1580mm
 Inside Width: 500mm
 Outside Width: 650mm
 Weight: 15kg



ADJUSTABLE FORKS

Blade: 600Lx75Wx20H
 lowers to 20mm
 Raises to 1500mm
 Inside Width: 6 to 500mm
 Outside Width: 156-650mm
 Weight: 34kg



SLIP ON PLATFORM

To suit fixed or Adjustable Forks
 Length: 700mm
 Width: 700mm
 Thickness: 3mm
 Weight: 14 kg



CRANE JIB

Lowers to 630mm,
 Raises to 2100mm
 350kg Max.Load@ 350mm
 300kg Max.Load@ 450mm
 250kg Max.Load@ 550mm
 Weight: 9kg

Part Number	Descriptions	Lift Height
Options		
# CJ-HY	Crane Jib-c.w Safety Hook	(2100mm-under hook 630mm)
# AF-HY	Forks - Adjustable	(1500mm)
# FF-HY	Forks - Fixed	(1580mm-lowered TBA)
# IF-HY	Forks - Inverted	(1980mm-lowered TBA)
# SOP-HY	Slip on Platform	(1580mm-lowered TBA)
# CBM/L-HY	Counterbalanced Multilift C/weight cost to be added - P.O.A.	-
# FSW-HY	Front Swivel Wheels	-
# WC-HY	Winch Cover	-
Modifications		
# NSEM-HY	Extend Mast up to an additional 1 Mtr. Only	(1500-2980mm)
# NSWB-HY	Widen Base	-

All prices/specifications subject to change without notice