

Replaces all previous versions

Effective 1st March 2005

Spring Balancers

KROMER spring balancers are designed to support heavy hand operated process tools and enable them to be operated with the minimum of effort.

Special Features

- ➔ Stops automatically if main spring fails
- ➔ Secondary safety chain for added security
- ➔ Stepless load balancing via worm gearing
- ➔ Replaceable high grade steel main spring
- ➔ CE conformance
- ➔ Cable limiters prevent overload damage
- ➔ Adjustable return stop and buffer
- ➔ Safety hook can be swivelled and adjusted laterally for alignment to work area
- ➔ Shock-resistant and non abrasive plastic internal housing



Model	Capacity (kg)	Stroke (m)	Weight (kg)
7200-1	0.3 - 1.2	1.2	0.5
7211-1	0.6 - 1.0	2	0.7
2	1.0 - 2.0	2	0.7
3	2.0 - 3.0	2	0.8
7212-1*	0.6 - 1.0	2	0.7
2	1.0 - 2.0	2	0.7
3	2.0 - 3.0	2	0.8
7221-1	3.0 - 5.0	2	2.9
2	4.0 - 6.0	2	3.0
3	6.0 - 8.0	2	3.1
4	8.0 - 10.0	2	3.3
7222-1*	3.0 - 5.0	2	3.2
2	4.0 - 6.0	2	3.3
3	6.0 - 8.0	2	3.4
33	3.0 - 5.0	3	3.3
36	6.0 - 8.0	4	3.6
4	8.0 - 10.0	2	3.6
7230-4	9.0 - 14.0	2	3.4
5	13.0 - 17.0	2	3.6
6	16 - 21	2	3.7
7231-4*	9.0 - 14.0	2	3.6
5	13.0 - 17.0	2	3.8
6	16 - 21	2	3.9
7235-1	15 - 25	2	25
2	25 - 35	2	26
3	35 - 45	2	26
4	45 - 50	2	26
7236-1*	15 - 25	2	25
2	25 - 35	2	26
3	35 - 45	2	26
4	45 - 50	2	26
7241-2	20 - 30	2	15.2
3	30 - 45	2	16.9
4	45 - 60	2	17.3
5	60.0 - 75.0	2	18.7
6	75.0 - 90.0	2	19.7
7	90.0 - 100.0	2	19.9

* Ratchet lock as standard

Model	Capacity (kg)	Stroke (m)	Weight (kg)
7251-1	15.0 - 25.0	3	25.0
2	25.0 - 35.0	3	26.0
3	35.0 - 50.0	3	27.0
4	50.0 - 65.0	3	28.0
5	65.0 - 80.0	3	29.0
6	80.0 - 90.0	3	30.0
7	90.0 - 100.0	3	31.0
8	100.0 - 115.0	3	42.0
9	115.0 - 130.0	3	44.0
10	130.0 - 140.0	3	46.0
11	140.0 - 150.0	3	48.0
7261-1	150.0 - 175.0	1.5	46.0
2	175.0 - 200.0	1.5	47.5
3	200.0 - 225.0	1.5	49.0
4	225.0 - 250.0	1.5	51.0
5	250.0 - 275.0	1.5	53.0
6	275.0 - 300.0	1.5	55.0

All prices/specifications subject to change without notice.