



Ultra IBC HardTop®

Comply With Regulations While Storing IBC Tanks Outdoors



- Upper roll-top door and lower swing-out doors combine to allow easy and convenient access to IBC.
- Safely stores an IBC tank with maximum dimensions of 1320 x 1320 x 1549 mm.
- Low profile (711 mm height), 1362 litre containment sump allows safe material handling and dispensing.
- Forkliftable, lockable, all-polyethylene design will not rust or corrode.
- **Helps meet new Stormwater Management Regulations — NPDES, 40 CFR 122.26 (1999).**
- **Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175.**



ULTRA-IBC HARDTOP	
Part# 1162: no drain	Weight: 238 kg
Part# 1161: with drain	Containment Capacity: 1362 litres
Outside Dimensions: 1638 x 1574 x 2438 mm	Uniformly Distributed Load: 3855 kg

U.S. Patent No. 5,615,608.

Ultra Twin IBC HardTop®

Outdoor Storage for Two IBC Tanks



- Uses same sump as Ultra-Twin IBC SpillPallet (see page 21).
- Unique, lockable, dual closure allows quick access to tanks.
- Roll-top covers can be easily lifted for routine visual inspection.
- Swing-out doors provide safety and convenience for loading/unloading tanks.
- Safely stores IBC tanks, with maximum dimensions of 1320 x 1320 x 1549 mm.
- **Meets Stormwater, SPCC and EPA Containment Regulations.**



ULTRA-TWIN IBC HARDTOP		
Part# 1148: no drain	Weight: 529kg	Sump Capacity: 2025 litres
Part# 1149: with drain		Weight Capacity: 3628 kg UDL/side
Dimensions: 3251 x 1701 x 2438 mm		
Option: Bucket Shelf, Part# 1160		