

NEW PRODUCT RELEASE.



AS4-1250 4 TONNE LIFT TABLE

Safetech introduces the AS4-1250 lift table

- Detailed product information
- Technical Specifications
- Product pictures
- A link to the Safetech website for further information

AS4-1250 LIFT TABLE

4000 kg's of lifting force with all of the quality and features present in other Safetech hydraulic lift tables. Designed and manufactured at our factory to Australian standards the AS4-1250 incorporates a safety bar, low-pressure hydraulics, internal power unit and a choice of controls. A wide range of options are available including the unique Safetech Smartlift controls, variable deck sizes and platforms, a range of surface treatments, IP 56 electrical installation, fork sockets or any one of the hundreds of customised options that Safetech has previously supplied.



Applications

- Manual palletising or depalletising
- Loading or unloading of stillages, containers, bins, bags, bricks, tiles
- Commonly used alongside conveyor, feeding hoppers, extruders, process and production equipment



Limitations

Maximum and minimum heights, loads greater than 4000 kg's.

Safety

The AS4-1250 is very safe to use but as with all scissor mechanisms care must be taken to avoid any entrapment as it is operated.

AS4-1250 Specifications

MODEL	CAP. (kg)	VERT. STROKE	MIN Ht	MAX HEIGHT	BASE WID.	BASE LEN.	ELEV TIME	POWER UNIT	WEIGHT
AS4-1250	4000	1250	310	1610	1850	2050	42	2.4kW 415/3/50	585
PLATFORM SIZES				STANDARD		MINIMUM		MAXIMUM	
				L	W	L	W	L	W
				2050	1850	2050	1768	2650	1950



 **SPACEPAC**
INDUSTRIES Pty. Ltd.
39 Ellen St. Wollongong NSW 2500, AUSTRALIA
Phone: +61 2 4227 3444 • 1300 763 444
Fax: +61 2 4226 2208 • ABN 98 002 454 462
spacepac@spacepac.com.au