



SPACEPAC

INDUSTRIES Pty. Ltd.

PO Box 1468 Auburn St. Wollongong NSW 2500

Phone: 1300 763 444 Fax: +61 2 4226 2208

Email: sales@spacepac.com.au ABN 98 002 454 462

WWW.SPACEPAC.COM.AU


MINUTE MISER™

3 WHEEL ELECTRIC UTILITY VEHICLE

550-lb Payload Capacity

Seating for Up to 2 Passengers

24-volt Powertrain



CUSHMAN™

Features and specifications of vehicles subject to change without notice.
Vehicle as photographed may include options not included on base model.



CUSHMAN™
LET'S WORK.™

SPACEPAC
INDUSTRIES Pty. Ltd.
PO Box 1468 Auburn St. Wollongong NSW 2500
Phone: 1300 763 444 Fax: +61 2 4226 2208
Email: sales@spacepac.com.au ABN 98 002 454 462
WWW.SPACEPAC.COM.AU

All work. All the time.

With the Cushman Minute Miser, you won't waste a second of your day. This versatile, energy-efficient vehicle is built to get you where you need to go quickly and safely. The Minute Miser features a flip-down seat for an additional passenger or a small cargo deck for moving equipment and materials. It is equipped with a zero-emissions, 24-volt electric powertrain and has a load capacity of 550 pounds to move you around your facility in moments. Trust the Minute Miser to get you to the next job quickly and efficiently.



MINUTE MISER 3 WHEELED ELECTRIC TRUCK

DIMENSIONS	
Overall Length	85.0 in (216 cm)
Overall Width	30.0 in (76 cm)
Overall Height (Tiller)	39.0 in (99 cm)
Overall Height (w/ optional Steering Wheel)	46.0 in (117 cm)
Wheel Base	48.0 in (122 cm)
Front Wheel Track	N/A
Rear Wheel Track	25.5 in (65 cm)
Ground Clearance	4.0 in (10 cm)
Cargo Deck Dimensions	23.0 in (58 cm) W x 29.0 in (73 cm) L
POWER	
Powertrain	24-Volt DC Series Wound
Horsepower (kW)	8.25 hp (6.15 kW) @ 1570 rpm
Electrical System	24-Volt DC
Batteries (Qty, Type)	Four, 6V Deep Cycle
Battery Charger	24 VDC, 100-240 VAC On-Board, UL & CE
Speed Controller	Solid State 250 Amp Rated
Drivetrain	Motor Shaft Direct Drive
Transaxle	Differential with Helical Gears
Gear Selection	Forward-Neutral-Reverse
Gear Shift Location	Dash Mounted
Rear Axle Ratio	14.78:1
PERFORMANCE	
Seating Capacity & Style	2-Person
Dry Weight (w/o Batteries)	440 lb (200 kg)
Curb Weight	690 lb (314 kg)
Cargo Deck Load Capacity	300 lb (140 kg)
Vehicle Load Capacity	550 lb (250 kg)
Outside Clearance Circle	10.8 ft (3.3 m)
Intersecting Aisle Clearance	54.0 in (137 cm)
Speed (level ground)	10 mph +/- 0.5 mph (14 kph +/- 0.8 kph)
STEERING & SUSPENSION	
Steering	Direct Handlebar to Front Fork
Front Suspension	Torque Block
Rear Suspension	Coil Springs & Single Shock Absorber
Service Brake	Rear Wheel Mechanical Drum
Parking Brake	Single Point Latch
Front & Rear Tires	4.80 x 8 (Load Range B)
FRAME & COLOR	
Frame & Body	Welded Steel with Powder-Coat Protection
Body & Finish	Diamond Plate. Polyester Primer and Acrylic
Standard Color	Safety Yellow

Factory Installed Options & Field Accessories

- Steering Wheel
- Foam Filled Tires
- Portable Charger
- Certification Module EE
- Hour Meter
- Headlight
- Horn
- CE Certification