

Specialty Ladders

Extra Heavy-Duty Shelf Ladders

- 1-1/2" wide angle aluminum feet with rubber treads.
- 4" deep slip-resistant ribbed steps.
- Tool holes in top cap for added convenience.
- All parts replaceable; ladders can be repaired at your facility.
- Each step braced front and back - 4 gussets and 16 rivets per step.
- Tapered for increased stability.
- Special padded tops for use against tank sides optional.
- Type 1A, 300 lb. duty rating.



Aluminum

MODEL	HEIGHT	BOTTOM WIDTH	LBS.
S100H-03	3'	21"	10
S100H-04	4'	22"	11
S100H-05	5'	24"	13
S100H-06	6'	25"	14
S100H-07	7'	26"	18
S100H-08	8'	28"	22
S100H-09	9'	29"	24
S100H-10	10'	31"	28
S100H-11	11'	32"	30
S100H-12	12'	33"	34
S100H-13	13'	35"	37
S100H-14	14'	36"	40
S100H-15	15'	38"	43
S100H-16	16'	39"	48
S100H-17	17'	41"	51
S100H-18	18'	42"	54
S100H-19	19'	43"	60
S100H-20	20'	45"	63

Fiberglass

MODEL	HEIGHT	BOTTOM WIDTH	LBS.
PS100H-03	3'	21"	11
PS100H-04	4'	22"	13
PS100H-05	5'	24"	15
PS100H-06	6'	25"	17
PS100H-07	7'	26"	21
PS100H-08	8'	28"	24
PS100H-09	9'	29"	28
PS100H-10	10'	31"	31
PS100H-11	11'	32"	35
PS100H-12	12'	34"	40
PS100H-14	14'	36"	48
PS100H-16	16'	39"	56

Security Access Ladders

- Locking device secures the ladder from unauthorized use.
- Opens to 12-1/2" wide when in use, and stores to only 2-1/2" wide in the closed, locked position.
- All aluminum construction facilitates use either indoors or out without worry of corrosion.
- Available with top (TP) or bottom (BP) locking device. Please specify when ordering. Padlock not included.

MODEL	OPEN LENGTH	HEIGHT TO TOP RUNG	LBS.
SAL-08	8' 11"	6' 10"	12
SAL-10	11' 2"	10' 0"	14
SAL-12	13' 4"	11' 3"	17
SAL-14	15' 7"	13' 6"	21
SAL-16	17' 10"	15' 9"	25
SAL-24	25' 8"	23' 8"	26



Specialty Ladders

Tank Inspection Ladders

- Designed for internal tank inspection and cleaning.
- Aluminum construction with replaceable 1-1/4" serrated rungs.
- 12" wide (13-5/8" over shoes) to facilitate entry into tank cars through narrow access hatches.
- Swivel safety shoes standard.
- Type 1A, 300 lb. duty rating.



MODEL	LENGTH	WIDTH	LBS.
TIL-08	8'	12"	12
TIL-10	10'	12"	15
TIL-12	12'	12"	18
TIL-14	14'	12"	21
TIL-16	16'	12"	24
TIL-18	18'	12"	27
TIL-20	20'	12"	30

Folding Inspection Ladders

- Designed for use in closed-in areas with extremely narrow access routes; i.e., inside storage tanks, manholes, water treatment plants, etc.
- Folds to 5-1/4" for easy maneuverability.
- Aluminum marine grade alloy construction.
- Safety shoes standard.
- Type 1A, 300 lb. duty rating.



MODEL	LENGTH		WIDTH		LBS.
	OPEN	CLOSED	OPEN	CLOSED	
FIL-08	8'	8'11"	15 1/2"	5 1/4"	14
FIL-10	10'	11'2"	15 1/2"	5 1/4"	16
FIL-12	12'	13'4"	15 1/2"	5 1/4"	19
FIL-14	14'	15'7"	15 1/2"	5 1/4"	23

Max Stack Ladders

- Sections can be combined to produce the desired length; ladder must be laterally supported every 30'.
- All aluminum construction reduces weight and resists corrosion.
- Each ladder section has a male and a female end to enable easy connection utilizing wing nuts and thumb screws.
- 16" wide to facilitate ease of handling and access through hatches and manholes.
- Bottom section requires heavy-duty aluminum swivel safety shoes with thick rubber tread for added slip-resistance.

MODEL	LENGTH	WIDTH	LBS.
MAX-03	3'	16"	14
MAX-04	4'	16"	17
MAX-05	5'	16"	20
MAX-06	6'	16"	23
MAX-07	7'	16"	26
MAX-08	8'	16"	29
MAX-09	9'	16"	32
MAX-10	10'	16"	35
MAX-12	12'	16"	41

Add an additional \$48.00 for safety shoes.



300 lb. Capacity

Aluminum Stepladders

Standard Features

- Industrial Type IA, 300 lb. duty rating.
- Meets and/or exceeds OSHA and ANSI A14.2 requirements as we interpret them.
- Manufactured of marine grade aluminum alloy for maximum strength.
- 4" deep slip-resistant ribbed steps for a more comfortable work surface.
- Large 1-1/2" wide aluminum angle feet with thick rubber tread.
- All components are field repairable which increases ladder life cycle and reduces costs.

Extra Heavy-Duty Platform Ladders 400H Series



- Large 14" X 17" embossed platform helps provide a comfortable, slip-resistant work surface on which to stand.

MODEL	PLAT. HT.	TOTAL HT.	OPEN DEPTH	BOTTOM WIDTH	LBS.
400H-02	2'	4'	31"	22"	20
400H-03	3'	5'	37"	23"	24
400H-04	4'	6'	42"	25"	29
400H-05	5'	7'	49"	26"	34
400H-06	6'	8'	55"	28"	38
400H-07	7'	9'	60"	29"	43
400H-08	8'	10'	66"	31"	47
400H-09	9'	11'	73"	32"	51
400H-10	10'	12'	79"	33"	56
400H-11	11'	13'	82"	35"	64
400H-12	12'	14'	89"	36"	71
400H-13	13'	15'	94"	38"	82
400H-14	14'	16'	99"	39"	83
400H-15	15'	17'	105"	41"	88
400H-16	16'	18'	111"	42"	95
400H-17	17'	19'	117"	44"	100
400H-18	18'	20'	122"	45"	107

Extra Heavy-Duty Double-Fronted Stepladders F900H Series



- Tool holes in top for added convenience.

MODEL	HEIGHT	OPEN DEPTH	BOTTOM WIDTH	LBS.
F900H-03	3'	31"	21"	18
F900H-04	4'	38"	22"	23
F900H-05	5'	45"	23"	28
F900H-06	6'	53"	25"	34
F900H-07	7'	60"	26"	39
F900H-08	8'	68"	28"	45
F900H-09	9'	75"	29"	51
F900H-10	10'	82"	31"	57
F900H-11	11'	90"	32"	63
F900H-12	12'	97"	33"	70
F900H-13	13'	105"	35"	74
F900H-14	14'	112"	36"	79
F900H-15	15'	120"	38"	84
F900H-16	16'	127"	39"	89

Extra Heavy-Duty Stepladders 100H Series



- Tool holes in top for added convenience.

MODEL	HEIGHT	OPEN DEPTH	BOTTOM WIDTH	LBS.
100H-03	3'	24"	21"	16
100H-04	4'	31"	22"	20
100H-05	5'	37"	23"	25
100H-06	6'	42"	25"	29
100H-07	7'	49"	26"	34
100H-08	8'	55"	28"	38
100H-09	9'	60"	29"	42
100H-10	10'	66"	31"	47
100H-11	11'	73"	32"	51
100H-12	12'	79"	33"	56
100H-13	13'	82"	35"	60
100H-14	14'	89"	36"	65
100H-15	15'	94"	38"	70
100H-16	16'	99"	39"	75
100H-17	17'	108"	41"	86
100H-18	18'	111"	42"	92
100H-19	19'	117"	44"	96
100H-20	20'	122"	45"	101

Fiberglass Stepladders

300 lb. Capacity

Extra Heavy-Duty Stepladders P100H Series



- Tool holes in top for added convenience.

Extra Heavy-Duty Double-Fronted Stepladders PF900H Series



- Tool holes in top for added convenience.

Extra Heavy-Duty Platform Ladders P400H Series



- Large 14" X 17" embossed platform provides a comfortable, slip-resistant work surface on which to stand.

Standard Features

- Industrial Type IA, 300 lb. duty rating.
- Meets and/or exceeds OSHA and ANSI A14.2 requirements as we interpret them.
- Non-conductive full channel fiberglass rail design adds extra safety when working around electricity.
- 4" deep slip-resistant ribbed steps for a more comfortable work surface.
- Large 1-1/2" wide aluminum angle feet with thick rubber tread.
- All components are field repairable which increases ladder life cycle and reduces costs.

MODEL	PLAT. HEIGHT	OPEN DEPTH	BOTTOM WIDTH	LBS.
P100H-03	3'	26"	21"	21
P100H-04	4'	31"	22"	24
P100H-05	5'	36"	24"	27
P100H-06	6'	42"	25"	33
P100H-07	7'	49"	26"	37
P100H-08	8'	55"	28"	40
P100H-09	9'	60"	29"	48
P100H-10	10'	66"	31"	53
P100H-11	11'	73"	32"	60
P100H-12	12'	79"	34"	67
P100H-14	14'	88"	36"	74
P100H-16	16'	99"	39"	82

MODEL	HEIGHT	OPEN DEPTH	BOTTOM WIDTH	LBS.
PF900H-03	3'	29"	21"	33
PF900H-04	4'	37"	22"	37
PF900H-05	5'	45"	24"	40
PF900H-06	6'	52"	25"	45
PF900H-07	7'	60"	26"	49
PF900H-08	8'	67"	28"	55
PF900H-09	9'	74"	29"	62
PF900H-10	10'	82"	31"	70
PF900H-11	11'	89"	32"	78
PF900H-12	12'	97"	34"	87
PF900H-14	14'	112"	36"	98
PF900H-16	16'	127"	39"	118

MODEL	PLAT. HT	TOTAL HT	OPEN DEPTH	BOTTOM WIDTH	LBS.
P400H-02	2'	4'	22"	31"	26
P400H-03	3'	5'	24"	36"	29
P400H-04	4'	6'	25"	42"	33
P400H-05	5'	7'	26"	49"	38
P400H-06	6'	8'	28"	55"	44
P400H-07	7'	9'	29"	60"	49
P400H-08	8'	10'	31"	66"	55
P400H-09	9'	11'	32"	73"	61
P400H-10	10'	12'	34"	79"	69
P400H-12	12'	14'	36"	88"	76
P400H-14	14'	16'	39"	99"	85

500 lb. Capacity

Aluminum Stepladders

Standard Features

- Exceeds OSHA requirements.
- Certified and tested to a 500 lb. load capacity.
- Manufactured of marine grade aluminum alloy for maximum strength.
- 4" deep slip-resistant ribbed steps for a more comfortable work surface.
- Large 1-1/2" wide aluminum angle feet with thick rubber tread.
- All components are field repairable which increases ladder life cycle and reduces costs.

Extra Heavy-Duty Platform Ladders 400H-HDC Series



- Large 14" x 17" embossed platform helps provide a comfortable, slip-resistant work surface on which to stand.

MODEL	PLAT. HT.	TOTAL HT.	OPEN DEPTH	BOTTOM WIDTH	LBS.
400H-HDC-03	3'	5'	37"	23"	25
400H-HDC-04	4'	6'	42"	25"	30
400H-HDC-05	5'	7'	49"	26"	35
400H-HDC-06	6'	8'	55"	28"	40
400H-HDC-07	7'	9'	60"	29"	45
400H-HDC-08	8'	10'	66"	31"	49
400H-HDC-09	9'	11'	73"	32"	54
400H-HDC-10	10'	12'	79"	33"	59

Extra Heavy-Duty Double-Fronted Stepladders F900H-HDC Series



- Tool holes in top for added convenience.

MODEL	HT.	OPEN DEPTH	BOTTOM WIDTH	LBS.
F900H-HDC-04	4'	38"	22"	23
F900H-HDC-05	5'	45"	23"	28
F900H-HDC-06	6'	53"	25"	34
F900H-HDC-07	7'	60"	26"	39
F900H-HDC-08	8'	68"	28"	45
F900H-HDC-09	9'	75"	29"	51
F900H-HDC-10	10'	82"	31"	57
F900H-HDC-11	11'	90"	32"	63
F900H-HDC-12	12'	97"	33"	70

Extra Heavy-Duty Stepladders 100H-HDC Series



- Tool holes in top for added convenience.

MODEL	HT.	OPEN DEPTH	BOTTOM WIDTH	LBS.
100H-HDC-03	3'	24"	21"	17
100H-HDC-04	4'	31"	22"	21
100H-HDC-05	5'	37"	23"	26
100H-HDC-06	6'	42"	25"	31
100H-HDC-07	7'	49"	26"	37
100H-HDC-08	8'	55"	28"	41
100H-HDC-09	9'	60"	29"	45
100H-HDC-10	10'	66"	31"	51
100H-HDC-11	11'	73"	32"	55
100H-HDC-12	12'	79"	33"	60

Fiberglass Stepladders

500 lb. Capacity

Extra Heavy-Duty Stepladders P100H-HDC Series



- Tool holes in top for added convenience.

Extra Heavy-Duty Double-Fronted Stepladders PF900H-HDC Series



- Tool holes in top for added convenience.

Extra Heavy-Duty Platform Ladders P400H-HDC Series



- Large 14" X 17" embossed platform provides a comfortable, slip-resistant work surface on which to stand.

Standard Features

- Exceeds OSHA requirements.
- Certified and tested to a 500 lb. load capacity.
- Manufactured of marine grade aluminum alloy for maximum strength.
- Non-conductive, full channel fiberglass rail design adds extra safety when working around electricity.
- 4" deep slip-resistant ribbed steps for a more comfortable work surface.
- Large 1-1/2" wide aluminum angle feet with thick rubber tread.
- All components are field repairable which increases ladder life cycle and reduces costs.

MODEL	PLAT. HT	OPEN WIDTH	OPEN DEPTH	LBS.
P100H-03-HDC	3'	26"	21"	22
P100H-04-HDC	4'	31"	22"	25
P100H-05-HDC	5'	36"	24"	28
P100H-06-HDC	6'	42"	25"	35
P100H-07-HDC	7'	49"	26"	38
P100H-08-HDC	8'	55"	28"	42
P100H-09-HDC	9'	60"	29"	50
P100H-10-HDC	10'	66"	31"	55
P100H-11-HDC	11'	73"	32"	63
P100H-12-HDC	12'	79"	34"	70

MODEL	HT	OPEN DEPTH	OPEN WIDTH	LBS.
PF900H-04-HDC	4'	37"	22"	40
PF900H-05-HDC	5'	45"	24"	49
PF900H-06-HDC	6'	52"	25"	57
PF900H-07-HDC	7'	60"	26"	66
PF900H-08-HDC	8'	67"	28"	74
PF900H-09-HDC	9'	74"	29"	82
PF900H-10-HDC	10'	82"	31"	91
PF900H-11-HDC	11'	89"	32"	99
PF900H-12-HDC	12'	97"	34"	108

MODEL	PLAT. HT	TOTAL HT	OPEN DEPTH	OPEN WIDTH	LBS.
P400H-04-HDC	4'	6'	25"	42"	33
P400H-05-HDC	5'	7'	26"	49"	38
P400H-06-HDC	6'	8'	28"	55"	44
P400H-07-HDC	7'	9'	29"	60"	49
P400H-08-HDC	8'	10'	31"	66"	55
P400H-09-HDC	9'	11'	32"	73"	61
P400H-10-HDC	10'	12'	34"	79"	69

Single & Extension Ladders

Standard Features

1-1/4" OD slip-resistant serrated aluminum rungs.

Large aluminum swivel safety shoes with thick rubber treads may be used in either tread or spike down position for improved traction in many environments.

All components are field repairable which increases ladder life cycle and reduces costs.

IND-F: Single Fiberglass Ladders

MODEL	LENGTH	WIDTH	LBS.
IND-F-410-08	8'	19 1/16"	26
IND-F-410-10	10'	19 1/16"	33
IND-F-410-12	12'	19 1/16"	37
IND-F-410-14	14'	19 1/16"	44
IND-F-410-16	16'	19 1/16"	51
IND-F-410-18	18'	19 1/16"	58
IND-F-410-20	20'	19 1/16"	65

IND-F: Fiberglass Extension Ladders

- Oversized 2-1/4" pulley and 1/2" poly rope allow easy operation

MODEL	UNEXTEND.	EXTEND.	WIDTH	LBS.
IND-F-420-16	8'7"	13'7"	22 5/16"	65
IND-F-420-20	10'7"	17'7"	22 5/16"	76
IND-F-420-24	12'7"	21'7"	22 5/16"	90
IND-F-420-28	14'7"	25'7"	22 5/16"	101
IND-F-420-32	16'7"	29'7"	22 5/16"	118
IND-F-420-36	18'7"	33'7"	22 5/16"	135
IND-F-420-40	20'7"	37'7"	22 5/16"	142

IND-A: Single Aluminum Ladders

MODEL	LENGTH	WIDTH	LBS.
IND-A-010-08	8'	19 1/16"	22
IND-A-010-10	10'	19 1/16"	28
IND-A-010-12	12'	19 1/16"	34
IND-A-010-14	14'	19 1/16"	41
IND-A-010-16	16'	19 1/16"	47
IND-A-010-18	18'	19 1/16"	53
IND-A-010-20	20'	19 1/16"	60

IND-A: Aluminum Extension Ladders

- Oversized 2-1/4" pulley and 1/2" poly rope allow easy operation

MODEL	UNEXTEND.	EXTEND.	WIDTH	LBS.
IND-A-020-16	8'5"	13'5"	22 1/4"	58
IND-A-020-20	10'5"	17'5"	22 1/4"	70
IND-A-020-24	12'5"	21'5"	22 1/4"	92
IND-A-020-28	14'5"	25'5"	22 1/4"	105
IND-A-020-32	16'5"	29'5"	22 1/4"	120
IND-A-020-36	18'5"	33'5"	22 1/4"	128
IND-A-020-40	20'5"	37'5"	22 1/4"	144

DLLH-S: Single Aluminum Ladders

MODEL	LENGTH	WIDTH	LBS.
DLLH-S-06	6'	20"	9
DLLH-S-08	8'	20"	12
DLLH-S-10	10'	20"	15
DLLH-S-12	12'	20"	18
DLLH-S-14	14'	20"	21
DLLH-S-16	16'	20"	24
DLLH-S-18	18'	20"	27
DLLH-S-20	20'	20"	30

DLLH-E: Aluminum Extension Ladders

- Oversized 2-1/4" pulley and 1/2" poly rope allow easy operation

MODEL	SECTION LENGTH	UNEXT. LENGTH	MAX. CLIMB LENGTH	WIDTH	LBS.
DLLH-E-16	16'	8'	13'	20"	28
DLLH-E-20	20'	10'	17'	20"	33
DLLH-E-24	24'	12'	21'	20"	38
DLLH-E-28	28'	14'	25'	20"	47
DLLH-E-32	32'	16'	29'	20"	52
DLLH-E-36	36'	18'	32'	20"	59
DLLH-E-40	40'	20'	35'	20"	64

500 lb. Capacity Fiberglass Single/Extension Ladders IND Series



Single & Extension Ladders

**500 lb. Capacity Aluminum
Single/Extension Ladders**
IND Series



**300 lb. Capacity Aluminum
Single/Extension Ladders**
DLLH Series



The 500 lb. duty rated fiberglass and aluminum IND series exceed all OSHA requirements as we interpret them.

The DLLH series is Type 1A, 300 lb. duty rated. Meets and/or exceeds ANSI and OSHA requirements as we interpret

Compact Storage Ladders



Standard Features

- Industrial Type I, 250 lb. duty rating.
- Meets and/or exceeds OSHA and ANSI requirements as we interpret them.
- Aluminum construction is lightweight, easy to carry and set up.
- Easily folds for compact storage.

Features

- Oversized 7" X 15" steps offer generous standing area, reducing fatigue when working at fixed heights for extended periods of time.

MODEL	PLATFORM HEIGHT	BOTTOM SIZE	PLATFORM SIZE	OVERALL HEIGHT	LBS.
FSS-1	2'	19" X 23"	7" x 15"	42"	13

Features

- Large 13-1/2" X 15" slip-resistant diamond tread platform provides a comfortable standing area.
- 30" high handrail provides an extra level of safety.

MODEL	PLATFORM HEIGHT	BOTTOM SIZE	PLATFORM SIZE	OVERALL HEIGHT	LBS.
SPL-1	2'	19" X 26"	13 1/2" x 15"	56"	15
SPL-2	3'	20" X 32"	13 1/2" x 15"	68"	18

Ladder Options



Top 2 steps painted red -- acts as a visual reminder to your employee NOT to over-climb.

Special I.D. tags -- identification tags provide permanent information for department, accounting code, inspection schedule, etc.



Tie-off rope -- can be used to increase ladder stability against tipping caused by worker over-reaching.

Stainless steel nuts and bolts -- improve service life in corrosive environments.



If you have other safety features that are your standards, let us know. We can do them!



39 Ellen St. Wollongong NSW 2500, AUSTRALIA
 Phone: +61 2 4227 3444 • 1300 763 444
 Fax: +61 2 4226 2208 • ABN 98 002 454 462
 spacepac@spacepac.com.au