



Replaces all previous versions

SAFETY DRUM VENTS / FILL UNITS

522 Drum Vent - For Vertical Drum



Mounts vertically in the 50mm (2") bung opening of 60 and 205 litre (55-gallon) drums.
 Automatic pressure relief opening between 5 and 8 psig and manual vacuum relief.
 Flame arrester prevents propagation of fire through vent passage.
 Available in brass with an aluminium plate flash arrester assembly or in all stainless steel.

Part Number	Description	Size (mm)	Test Lab	Trade Exc.GST
# 522-PR	Brass	50mm Male NPS	FM	
# F5522	316 S/Steel			

525 Drum Vent - For Horizontal Drum



This 19mm (3/4") Drum Vent provides continuous, safe venting of storage drums when the 50mm (2") bung opening is not available. Perforated-metal flash arrester prevents flashbacks through the vent.
 Protective hood shields flash arrester and prevents dust and dirt from entering the drum.

Part Number	Description	Size (mm)	Test Lab	Trade Exc.GST
# 525-PR	Brass	19mm Male NPS	FM	

5522 Drum Vent - For Horizontal Drum



Automatic pressure relief at approximately 5 psig. Manual vacuum relief. In case of an external fire, the fusible emergency relief plug melts venting pressure and preventing drum rupture.
 Perforated-metal flash arrester prevents accidental ignition of vapor within the drum.

Part Number	Description	Size (mm)	Test Lab	Trade Exc.GST
# 5522-PR	Brass	50mm Female NPS	FM	
# E1953	316 S/Steel	50mm for horizontal drum		

Please email to spacepac@spacepac.com.au for current pricing.

Note: Additional Freight Charge Ex-Factory

All prices/specifications subject to change without notice.

ADD 10% GST AUSTRALIA ONLY