



Ultra SpillBerm®

Temporary Berm Seals Off Spills From The Environment, Nearby Drains And Doorways



Part# 2100


- Standard 3048 mm sections can be cut to various lengths to meet custom needs.
- Unique, urethane material “weeps” into small cracks and crevices to seal off liquid flow.
- SpillBerm is non-absorbing and is easily cleaned for repeated use.
- Applications include:
 - Spill response
 - Temporary secondary containment
 - Sealing off of doorways during washdown operations
- Flexible Ultra-SpillBerm will bend and turn to form almost any shape while temporarily “bonding” to any smooth surface.

• **Helps comply with NPDES and SPCC.**

Decide what shape or configuration is required and use optional Connectors and 90° Corners to complete the area.



ULTRA-SPILLBERM
Part# 2100: Orange • Part# 2050: Black
Dimensions: 3048 x 101 x 57 mm
Weight: 14 kg per unit
Material: Non-absorbing polyurethane
Optional Connectors (Part# 2101) used to connect 3048 mm sections
Optional Corners (Part# 2102) are used with Connectors to make 90° corners



U.S. Patent No. 5,236,281

Ultra SpillBerm Plus®

Taller SpillBerm Helps Contain or Divert Larger Volume Spills

- Flexible polyurethane construction is non-absorbent and chemical resistant — easily cleans with soap and water for repeated uses.
- Built-in connectors allow multiple 1524 mm units to be quickly and easily connected.
- **Helps comply with NPDES and SPCC.**

ULTRA-SPILLBERM PLUS
Part# 2054
Dimensions: 1524 x 101 x 114 mm
Weight: 7 kg per unit
Material: Non-absorbing polyurethane

U.S. Patent No. 5,236,281



Part# 2054

