

Versigen

The Catering Equipment
Company



Versicarte Plus
September 2008

Versigen



Removable grid shelves make cleaning easy and in heated and refrigerated units help air circulation.



Coiled flex keeps electrical connection tidy. Hooking the flex to the unit improves portability.

Versicarte Plus

Versigen's **Versicarte** food service trolleys have been totally redesigned to meet your changing needs. The new **Versicarte Plus** range has been developed in consultation with catering organisations, so as well as helping caterers comply with hygiene, HACCP, energy efficiency and healthy eating initiatives, these great-looking food service trolleys will help attract customers to your meal service.

Food safety and quality have always been at the heart of the Versicarte. The **Versicarte Plus** further enhances this; for example, hot cupboards are now fan-assisted to give fast, even heating and ensure the best quality.

And the famous **Versicarte** versatility has been further expanded. Innovative features include the glass screens that can be adjusted, so that the trolley can switch from self-service to assisted service easily.

The wide range of options allows most modules to be customised to your individual requirements.



All Versicarte Plus units can be fitted with the option of a triple tube drop down tray slide or solid drop down tray slide

Gantry lighting is fitted with safety bulbs featuring an outer glass casing.

Versicarte modules can be butted together to form a straight or angular service counter. Alternatively, stand alone units can be placed around the dining area to create a free-flow self-service environment.

The new trolleys' streamlined design, including curved gantry, smooth body and semi obscured castors, is not just highly practical: the stylish lines will appeal directly to your young customers. What's more, the **Versicarte Plus** fascia panels can be easily changed. So if you want a fresh look in the dining area, simply change the panels for a new colour scheme!

New products in the range include the **Versicarte Plus** Salad Bar, designed to keep those healthy greens looking great and in tip-top condition.

The Versatile new **Versicarte Plus**: making food service as easy as A, B, C.

2	Versicarte Plus
4	Finishes
5	Hot Top
5	Dry Heat Bains Marie
6	Refrigerated Display Refrigerated Well
7	Cold Well/Polar Plates
8	Salad Bar
9	Storage/Hot Cupboard
10	Cashier/Split Level/ Corner Units
11	Low Level Versicarte Plus



Glass panel in self service position



Glass panel in assisted service position



Lockable castors make moving and positioning of units effortless



Optional extras such as this menu holder can be added to each unit



Versicarte Plus Finishes


Versicarte Plus's unique design enables a vast range of colours and finishes to be supplied, below are a sample of our Standard Range. Metallics, woods and natural textures are also available on request.



Various colours shown with non standard colours & wood finishes priced on application.

Coachlines and transfers are also available at extra cost.

Samples of our Standard Colour Coated Steel Finishes

				
Aztec Yellow	Black	Forest Green	Goosewing Grey	Academy Maple
				
Merlin Grey	Ocean Blue	Pacific Blue	Poppy Red	American Natural
				
Regatta Blue	Spritzer	Stainless Steel	Terracotta	Mahogany
				
Vandyke Brown	Verona	Wedgewood Blue	White	Russian Maple

Whilst every effort is made to represent the true colours of our panels these must be used as a guide only. True colour samples are available upon request.



Optional Solid Drop Down Tray Slide



Optional Triple Tube Drop Down Tray Slide



VCBM4 - shown with optional triple tube drop down tray slide and coach lines. Gantry shown in self service position.



VCHT4 - Shown with optional triple tube drop down tray slide and coach lines. Gantry shown in self service position.

Hot Top, Inset with Glass Thermal Panels, plus Hot Cupboard
 Models VCHT2, VCHT3, VCHT3, VCHT4

- Store hot food ready for serving.
- Illuminated on/off switch indicates power is on.
- Top inset with toughened glass thermo panels with variable temperature control up to approximately 110°C.
- Thermostatically controlled hot cupboard with fan-assisted heating unit.
- Sliding doors and all internal grid shelves are removable for cleaning.
- Cupboard heating unit can easily be removed for maintenance and cleaning.
- Optional heated gantry with interchangeable curved glass screen. Quartz heated gantry with illuminated on/off switch



Rear view of hotcupboard

Dry Heat Bains Marie with Hot Cupboard
 Models VCBM2, VCBM3, VCBM4, VCBM5

- Store hot food ready for serving.
- Illuminated on/off switch indicates power is on.
- Thermostatically controlled Bain-marie with fan-assisted heating unit.
- Designed to accommodate various combinations of interchangeable Gastronorm pans up to 150mm deep all Gastronorm pans sold separately please see price list for details.
- Sliding doors and internal grid shelves are removable for easy cleaning and maintenance.
- Optional heated gantry with interchangeable curved glass screen. Quartz heated gantry with illuminated on/off switch



Optional menu display holder. Please see price list for details.



Removeable grid shelves.



VCCP optional lift off carving plate to suit thermo glass panel. Please see price list for details.

VCHT2	VCHT3	VCHT4	VCHT5	VCBM2	VCBM3	VCBM4	VCBM5
55	82	110	137	45	67	90	112
830	1160	1490	1815	830	1160	1490	1815
1310	1310	1310	1310	1310	1310	1310	1310
680	680	680	680	680	680	680	680
950	950	950	950	950	950	950	950
740	740	740	740	740	740	740	740
900	900	900	900	900	900	900	900
2.1	2.5	2.7	3.1	2.45	2.65	2.9	3.1
1.9	2.1	2.3	2.5	2.25	2.25	2.5	2.5
-	-	-	-	2	3	4	5
2	3	4	5	-	-	-	-
3	3	3	3	3	3	3	3

MODEL
Weight kg
Length mm
Height including gantry mm
Depth mm
with trayslide up
with trayslide down
Work surf. Ht. mm
Power rating kw including gantry excluding gantry
1/1 Gastronorm Capacity
No. of Gastronorm panels
Hot cupboard under

All electrical units under 3kw complete with mains lead and 13 amp plug.



SPACEPAC

INDUSTRIES Pty. Ltd.

PO Box 1468 Auburn St. Wollongong NSW 2500

Phone: +61 2 4227 3444 • 1300 763 444

Fax: +61 2 4226 2208 • ABN 98 002 454 462

www.spacepac.com.au



VCRD4 - Shown with optional triple tube drop down tray slide.



Rear view of VCRD4R. Shown with refrigerated storage cupboard.

Note: All refrigerated units are available with refrigerated storage cupboard. Add R to the standard code.

Note: Refrigerated units are designed for straight through ventilation. If units are to be placed against a wall alternative ventilation arrangements are available at extra cost.

Refrigerated Multi-Tier Display Unit with Ambient Shelf Under

Models VCRD3, VCRD4, VCRD5

- Refrigerated multi tier display unit with chilled well, three glass adjustable shelves and ambient shelf under.
- Curtain of cold re-circulating air cascades down from top, ensuring even temperature of 2C to 8C.

WARNING

These units are not designed to operate in full mode for more than 24 hours, unless an optional front blind has been fitted.

- If the unit is to be used over a 24 hour period with the optional front blind, the blind should be pulled down as soon as possible after service has stopped.
- Stream of re-circulating cold air is blown up and across the display shelves and chilled well, ensuring temperature is maintained safely
- Glass display shelves are removable and have adjustable brackets.
- Chilled well has removable base sections for easy cleaning and maintenance.
- Automatic defrost cycle.
- Pull out condensate drip tray.

On units with Refrigerated Storage Cupboard under

- Storage cupboard with fan-assisted refrigeration.
- Internal mid and base shelves are removable for easy cleaning.
- Hinged doors seal cupboard with magnetic gaskets.



VCRW4 - Shown with optional coach lines and solid drop down tray slide. Gantry shown in assisted service position.

Refrigerated Well with Ambient Shelf Under

Models VCRW3, VCRW4, VCRW5

- Refrigerated blown air well complete with ambient shelf under and optional illuminated gantry with interchangeable glass screen.
- Re-circulating cold air blows across the display well ensuring an even temperature of 2C to 8C.
- Chilled well has removable base sections for easy cleaning and maintenance.
- Automatic defrost cycle.
- Pull out condensate drip tray.

On units with Refrigerated Storage Cupboard under

- Storage cupboard with fan-assisted refrigeration.
- Internal mid and base shelves are removable for easy cleaning.
- Hinged doors seal cupboard with magnetic gaskets.

Performance

MODEL	VCRD3 VCRD4 VCRD5			VCRD3R VCRD4R VCRD5R			VCRW3 VCRW4 VCRW5			VCRW3R VCRW4R VCRW5R		
	Refrigerated Display	Ambient Shelf Under		Refrigerated Display	Refrigerated Storage Cupboard		Refrigerated Display	Ambient Shelf Under		Refrigerated Display	Refrigerated Storage Cupboard	
Weight kg	156	208	260	156	208	260	127	170	212	127	170	212
Length mm	1160	1490	1815	1160	1490	1815	1160	1490	1815	1160	1490	1815
Height including gantry mm	1640	1640	1640	1640	1640	1640	1310	1310	1310	1310	1310	1310
Depth mm	680	680	680	680	680	680	680	680	680	680	680	680
with trayside up	950	950	950	950	950	950	950	950	950	950	950	950
with trayside down	740	740	740	740	740	740	740	740	740	740	740	740
Work surf. Ht. mm	900	900	900	900	900	900	900	900	900	900	900	900
Power rating kw including gantry excluding gantry	2.0 -	2.0 -	2.0 -	2.0 -	2.0 -	2.0 -	1.0 0.75	1.0 0.75	2.0 1.75	1.0 0.75	1.0 0.75	2.0 1.75
1/1 Gastronom capacity	3	4	5	3	4	5	3	4	5	3	4	5
Refrigerated storage cupboard under	-	-	-	3	3	3	-	-	-	3	3	3

See price list for detailed specification

OPERATING CONDITIONS FOR REFRIGERATED WELL AND MULTI TIER DISPLAYS

IMPORTANT

To obtain the maximum performance and efficiency from these units it is imperative that the ambient room conditions where the units are being used do not exceed a temperature off 25c or exceed a relative room humidity of 50%.

WARNING

Should conditions exceed the above? The display units will not maintain food temperatures at required levels E&R Moffat cannot accept responsibility for the performance of the units being used in extreme conditions.

- Do not install units in draughty conditions where the air movement is greater than 0.2mtr./sec. (For example near entrance/ exit doors, open windows, under air conditioning vents or ceiling mounted fan).
- Do not install units where there is high solar radiated heat (for example, direct sunlight, room heaters or bright spotlights)
- When loading refrigerated display units for best performance and refrigeration efficiency a gap should be left between the products allowing the cold air to pass through and re-circulate.



Optional Solid Drop Down Tray Slide



Optional Triple Tube Drop Down Tray Slide



VCPW4 - Shown with optional standard triple tube drop down tray slide.



Polar Plates

Polar plates must firstly be charged for 12/24 hours in a deep freeze. They are then placed inside the well where they give off a steady flow of cold air for a minimum of two hours. Once used, other polar plates can then be substituted thus keeping the well cold.



Interior view of polar well.

Polar Well with Polar Plates and Ambient Storage Cupboard Underneath

Models VCPW2, VCPW3, VCPW4, VCPW5

- Polar well supplied with E&R Moffat Polar Plates, ambient storage cupboard, optional illuminated gantry and interchangeable glass screen.
- Polar Plates keep food chilled for 2 to 3 hours. Before use, the Polar Plates are charged for 8 to 12 hours in a deep freeze. If longer periods of operation are required, extra Polar Plates can be charged and used in rotation.
- Storage cupboard sliding doors are removable for easy cleaning.
- All internal shelves are removable for cleaning.
- Optional illuminated gantry with on/off switch indicating power is on.

Performance

	VCPW2	VCPW3	VCPW4	VCPW5	MODEL
	58	87	117	145	Weight kg
	830	1160	1490	1815	Length mm
	1310	1310	1310	1310	Height including gantry mm
	680	680	680	680	Depth mm
	950	950	950	950	with tray slide up
	740	740	740	740	with tray slide down
	900	900	900	900	Work surf. Ht. mm
	0.026	0.026	0.026	0.026	Power rating kw including gantry
	-	-	-	-	excluding gantry
	2	3	4	5	No. of 1/1 Polar Plates
	-	-	-	-	Refrigerated storage cupboard under

All electrical units under 3kw complete with mains lead and 10/15 amp plug.



SPACEPAC

INDUSTRIES Pty. Ltd. www.spacepac.com.au

PO Box 1468 Auburn St. Wollongong NSW 2500

Phone: +61 2 4227 3444 • 1300 763 444

Fax: +61 2 4226 2208 • ABN 98 002 454 462



VCPW3C - Shown with c/w canopy, Optional Triple Tube Drop Down Tray Slides to both sides and two optional Plain Salad Bar Shelves (fully adjustable) and optional coachlines.

- Salad Bar models are supplied c/w Salad Bar Canopy with choice of decorative finish.
- Drop Down Tray Slides to one or both sides, Canopy Shelves and End Shelves are extra (see price list).



Salad bar Canopy can have any picture or logo added at no extra cost



Optional Salad Bar Shelves Fully adjustable.

VCPW3C - shown c/w Canopy and optional Solid Drop Down Tray Slide to one side and one optional Plain Salad Bar Shelf (fully adjustable) and one optional Versicarte Plus End Shelf.



Optional Island Adjustable Shelf

VCPW3C - shown c/w Canopy and optional Triple Tube Drop Down Tray Slides to both sides and optional Salad Bar Island Shelf (fully adjustable) and optional transfers.



Polar Plates

Polar plates must firstly be charged for 12/24 hours in a deep freeze. They are then placed inside the well where they give off a steady flow of cold air for a minimum of two hours. Once used, other polar plates can then be substituted thus keeping the well cold.

Interior view of polar well.

Performance

MODEL	Blown Air Refrigerated Salad Bar Ambient Shelf Under			Blown Air Refrigerated Salad Bar Refrigerated Storage Cupboard Under			Polar Plate Salad Bar Ambient Shelf Under			
	VCRW3C	VCRW4C	VCRW5C	VCRW3RC	VCRW4RC	VCRW5RC	VCPW2C	VCPW3C	VCPW4C	VCPW5C
Weight kg	137	180	222	137	180	222	68	97	127	155
Length mm	1160	1490	1815	1160	1490	1815	830	1160	1490	1815
Height including canopy mm	1880	1880	1880	1880	1880	1880	1880	1880	1880	1880
Depth mm	680	680	680	680	680	680	680	680	680	680
with tray slides up	1220	1220	1220	1220	1220	1220	1220	1220	1220	1220
with tray slides down	800	800	800	800	800	800	800	800	800	800
Work surf. Ht. mm	900	900	900	900	900	900	900	900	900	900
Power rating kw including canopy	1.0	1.0	2.0	1.0	1.0	2.0	0.026	0.026	0.052	0.052
1/1 Gastronorm capacity	3	4	5	3	4	5	2	3	4	5
Refrigerated storage cupboard under	-	-	-	3	3	3	-	-	-	-

See price list for detailed specification.

Note: Refrigerated units are designed for straight through ventilation. If units are to be placed against a wall alternative ventilation arrangements are available at extra cost.



VCSC4 with optional triple tube drop down tray slide and transfers.



Optional Solid Drop Down Tray Slide



Optional Triple Tube Drop Down Tray Slide

Ambient Storage Cupboard With Plain Top

Model's VCSC2, VCSC3, VCSC4, VCSC5

- Sliding doors are removable for easy cleaning.
- All internal grid shelves are removable for cleaning.
- Optional illuminated gantry with on/off switch indicating power is on, complete with interchangeable curved glass screen.



VCHC4 with optional coach lines and solid drop down tray slide.



Rear view of storage cupboard.



Internal fan.

Hot Cupboard

Model's, VCHC2, VCHC3, VCHC4, VCHC5

- Hot cupboard can store pre-heated food for serving.
- Thermostatically controlled hot cupboard with fan assisted removable heating unit.
- Sliding doors are removable for easy cleaning.
- All internal grid shelves are removable for cleaning.
- The heating unit (located on the base of the cupboard) can easily be removed for maintenance and cleaning.
- Optional quartz heated gantry with interchangeable curved glass screen.

VCSC2	VCSC3	VCSC4	VCSC5
30	45	60	75
830	1160	1490	1815
1310	1310	1310	1310
680	680	680	680
950	950	950	950
740	740	740	740
900	900	900	900
0.026	0.026	0.052	0.052
-	-	-	-
2	3	4	5


VCHC2	VCHC3	VCHC4	VCHC5
34	51	68	85
830	1160	1490	1815
1310	1310	1310	1310
680	680	680	680
950	950	950	950
740	740	740	740
900	900	900	900
1.7	1.9	1.9	2.1
1.5	1.5	1.5	1.5
2	3	4	5

MODEL
Weight kg
Length mm
Height including gantry mm
Depth mm
with tray slide up
with tray slide down
Work surf. Ht. mm
Power rating kw including gantry
excluding gantry
1/1 Gastronorm capacity

All electrical units under 3kw complete with mains lead and 10/15 amp plug.



VCCSR right handed cashier section with optional triple tube drop down tray slide.



Computer port in work surface



Optional lockable cash drawer

Cashier Section with Cable Port and Double Electrical Socket

Model's, VCCS(R), VCCS(L)

(R) denotes right handed, (L) denotes left handed

- Suitable for most types of cash registers, barcode scanners and Epos systems.
- Fitted with a cable port and double electric socket as standard.
- Complete with sloping rubber footrest.



Transposable Right Angle Corner Section

Model VCCU - Shown with optional triple tube drop down tray slide


- Transposable right angle corner section creating a 90° change in direction.



Low Level Infill Unit

Model VCSL

- Low unit can be used to create a split level effect when used in line with any other unit in the range.
- Storage space underneath.



Performance

MODEL	VCCS(R)	VCCS(L)	VCCU	VCSL
Weight kg	62	62	72	25
Length mm	1160	1160	1380	680
Height including gantry mm	-	-	-	-
Depth mm	680	680	480	680
with tray slide up	950	950	750	-
with tray slide down	740	740	540	-
Work surf. Ht. mm	900	900	900	500
Power rating kw including gantry	-	-	-	-
excluding gantry	-	-	-	-
No. of panels	-	-	-	-

See price list for detailed specification

Low level Versicarte Plus

Low level modules designed for use with younger children. Advantages include the easy and safe viewing of food. Designs such as cartoon characters and logos can be applied using durable vinyl. All the specifications and options, as per full size modules, are available. Low level Versicarte Plus units are 800mm high to the work surface.

Note: Refrigerated units are designed for straight through ventilation. If units are to be placed against a wall alternative ventilation arrangements are available at extra cost.



Optional Solid Drop Down Tray slide



Optional Triple Tube Drop Down Tray slide



VCBM4(B) shown with optional triple tube drop down tray slide and transfers.

All Versicarte units are available as low level units for children. Add "B" to standard code ie VCBM4(B). Height = 800mm.



Coachlines and bespoke designs can be incorporated at extra cost.



Above - Low level Versicarte Plus height comparison with full size module