

# Spacepac Extra Heavy Duty Castors









Our extra heavy duty castors series, load range from 3 tons to 10 tons, which can meet the demand of heavy industrial equipment and mechanical handling scheme.

16mm high-quality thickened base plate and 12mm thickened support can meet the load-bearing requirements of most industrial equipment.

The wheel tread is made of high-quality polyurethane material, with a hardness of 98 shore A.

The cast iron surface treatment and polyurethane bonding process are operated by technicians with more than 20 years' experience in the castor industry.

The refinement of the process improves the quality and bearing capacity of the whole heavy-duty castor, and extends the service life of the castors.

Pictures	Descriptions	Part Number					
			Load Capacity (kg)	Wheel Size (mm)	Total Height (mm)	Top Plate (mm)	Hole Distance (mm)
	Swivel castor, High Quality PU on solid steel core wheel, extra thickness housing.	90S/HEU150.150	3000	150 x 120	245	255 x 200	210 x 160
		90S/HEU200.150	5000	200 x 120	300	250 x 200	210 x 160
		90S/HEU250.150	8000	250 x 150	370	300 x 250	250 x 200
		90S/HEU300.150	9500	300 x 150	420	200 x 250	250 x 200
	Fixed Castor, High Quality PU on solid steel core wheel, extra thickness housing.	90R/HEU150.150	3000	150 x 120	245	255 x 200	210 x 160
		90R/HEU200.150	5000	200 x 120	300	250 x 200	210 x 160
		90R/HEU250.150	8000	250 x 150	370	300 x 250	250 x 200
		90R/HEU300.150	9500	300 x 150	420	200 x 250	250 x 200
	Swivel with thumb brake castor, High Quality PU on solid steel core wheel, extra thickness housing.	90T/HEU150.150	3000	150 x 120	245	255 x 200	210 x 160
		90T/HEU200.150	5000	200 x 120	300	250 x 200	210 x 160
		90T/HEU250.150	8000	250 x 150	370	300 x 250	250 x 200
		90T/HEU300.150	9500	300 x 150	420	200 x 250	250 x 200

Features shown are subject to change without notice

Contact us at [sales@spacepac.com.au](mailto:sales@spacepac.com.au) or on 1300 763 444 for more information